



Easy-Drive Tiller



Front LED Lights and Indicators

The Pathrider® 10 Deluxe 2.0 Scooter delivers the same great performance you love, with new, contemporary features. Frosted headlights offer a touch of style while providing optimal illumination. An integrated USB charging port in the tiller allows you to power your smart device while on the go, and the convenient storage/cup holder in the tiller keeps your items close at hand. With Pride's signature feathertouch disassembly and front and rear suspension, the Pathrider® 10 Deluxe 2.0 is a new class of scooter.









PRIDE® MOBILITY SCOOTERS LIVE YOUR BEST®

Specifications 4w: S710DX2

Weight Capacity	350 lbs. (160 kg)
Maximum Speed ¹	Up to 5.5 mph (9 km/h)
Ground Clearance ²	3.25" (9 cm) (at midframe)
Turning Radius ²	52.5" (134 cm)
Overall Length ²	47.25" (120 cm)
Overall Width ²	22.25" (56cm)
Seat-to-Ground	23"-25" (58-64 cm)
Seat-to-Deck	16.5"-19" (42-48 cm)
Front Tyres	3.6" x 10.6" (9.1 cm x 26.9 cm) solid
Rear Tyres	3.6" x 10.6" (9.1 cm x 26.9 cm) solid
Suspension	Front and Rear
Range Per Charge ^{2,4}	Up to 16 miles (30 km)
Total Weight Without Batteries	170.25 lbs. (78 kg)
Heaviest Piece When Disassembled	66.5 lbs. (30.25 kg) front section
Standard Seating	Type: Reclining high-back seat with headrest Weight: 42 lbs. (19 kg) Material: Black Vinyl Dimensions: Width: 17.5" (44.5 cm) Depth: 17" (43.2 cm)
Motor Output	Rear-wheel drive, sealed transaxle, 24-volt DC motor
Brakes	Regenerative and electromechanical
Battery Requirements ^{3,5}	Two 12-volt, deep cycle Size: 40 AH Weight: 32.75 kg (14.75 kg) each
Battery Charger	Off-board, 5 amp
Colour	Viper Blue

Features

- New contemporary tiller design with advanced features:
 - New under tiller puddle light
 - New integrated storage/cup holder in tiller
 - New integrated USB mobile device charging port in tiller
 - New frosted LED headlights, low-mounted LED pathway light and LED indicators brighten your route
 - New ambient voltmeter adjusts brightness to suit your environment
 - Easy access tiller-mounted charger port for standard dual voltage off-board charger
- Exclusive one-hand feather touch disassembly provides the ultimate quick transport system
- Easy-drive tiller with wraparound handles
- Standard rearview mirror



New Tiller Design

Options

- Double crutch holder
- Oxygen tank holder
- Rear basket
- Additional rearview mirror
- 1 Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tyre condition.
- 2 Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or 3%).
- 3 AGM or ael cell type required.
- 4 Battery weight may vary based on manufacturer.
- 5 Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 7176-4 standards.
 Results derived from theoretical calculations based on battery specifications and drive system performance test conducted at maximum weight capacity.

NOTE: All specifications subject to change without notice.

INCLE ALL SPECIFICATIONS SUBJECT TO CRIANGE WITHOUT NOTICE.

The information contained herein is correct at the time of publication; due to Pridé's commitment to constant improvement and development, we reserve the right to alter specifications without prior notice. Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct type pressures, ambient temperature, and the gradient and surface of the road or pavement. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.











